

3.2" Color TFT LCD, supporting photo/video, time/date display and multi-languages. Video and images can also be transferred to your PC via the SD Card or USB cable(included). Waterproof(IP67) flexible gooseneck retains configured shape.



EMC
EN: 61326



Specifications			
	BS-150	BS-150B	BS-151
LCD screen type	3.2" TFT	3.2" TFT	3.5" TFT
LCD Pixels	320x240		
The max number of frames(FPS)	30FPS/S		
Picture format from the camera	JPG(640x480)		
Camera video format	3GP	AVI(720x240)	MP4(640x480)
Gooseneck length	1m(39")		
Camera diameter	17mm(0.66")		
Viewing distance	5cm to 15cm		
Viewing angle	68°		
Zoom			2.0X
Rotation		Mirror 180°	90°
SD card	Max 8GB	2GB/Max 8GB	
Working voltage	Li Battery 3.7V/1800mA		
TV-OUT	PAL/ NTSC	NTSC	PAL/ NTSC
Language	Support English, French, German, Spanish		



Size(HxWxD): 240mm x 160mm x 100mm

Weight: 584g

Accessories:

3.7V Li battery, power adaptor, USB cable, mirror, hook, magnet, gift box with carrying case.

Model 151

Model 150



Size(HxWxD): 240mm x 160mm x 100mm

Weight: 584g

Accessories:

3.7V Li battery, power adaptor, mirror, hook, magnet, gift box with carrying case.

Model 101



Size(HxWxD): 240mm x 160mm x 100mm

Weight: 584g

Accessories:

3.7V Li battery, power adaptor, mirror, hook, magnet, gift box with carrying case.

Model 100

Features

- Support real-time live view
- TV peripherals to support operations in other devices
- Highlighted with LED to support the operation in the dark
- Built-in 1800mAh lithium battery, support USB charging
- Standby function to support the charge
- Support rotating the image 180° from top to bottom
- Flexible gooseneck imager head with waterproof
- 3.5" Color TFT LCD
- Camera and Video function

Specifications

LCD screen type	3.5" TFT
LCD Pixels	320x240
The max number of frames(FPS)	30FPS/S
Gooseneck length	1m(39")
Camera diameter	17mm(0.66")
Viewing distance	5cm to 15cm
Viewing angle	68°
Zoom	2.0X
Working voltage	Li Battery 3.7V/1800mA
TV-OUT	PAL/NTSC system

Features

- Support real-time live view
- TV peripherals to support operations in other devices
- Highlighted with LED to support the operation in the dark
- Built-in 1800mAh lithium battery, support USB charging
- Standby function to support the charge
- Support rotating the image 180° from top to bottom
- Flexible gooseneck imager head with waterproof
- 3.0" Color TFT LCD

Specifications

LCD screen type	3.0" TFT
LCD Pixels	960x240
The max number of frames(FPS)	30FPS/S
Gooseneck length	1m(39")
Camera diameter	17mm(0.66")
Viewing distance	5cm to 15cm
Viewing angle	68°
Working voltage	Li Battery 3.7V/1800mA
TV-OUT	PAL/NTSC system