




## GD-3303

Refrigerant Leak Detector 16" inch Gooseneck detector is easy to measure the hard-reached areas. Highly sensitive and reliable Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak. Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate. Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.



<b>Features</b>	
16" inch Gooseneck detector is easy to measure the hard-reached areas.	
Highly sensitive and reliable	
Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.	
Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.	
Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.	

<b>Specifications</b>	
Pump driven field adjustable range	10ppm
Sensor Type	Solid State
Alarm	Visible & Audible at 10% LEL for Refrigerant Leaks. Can be calibrated for other concentrations or gases.
Warm-Up	Approx. 1 minute
Response Time	Less than 2 sec. (up to 40% LEL)
Duty Cycle	Intermittent
Probe Length	16"
Battery	3 "C" Alkaline



**Refrigerant Leak Detector**

16" inch Gooseneck detector is easy to measure the hard-reached areas.

Highly sensitive and reliable

Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.

Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.

Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.

Size (H x W x D): 221mm x 72mm x 46mm  
 Weight: 498g