



## K 250 Hand-operated cutting tool for Al and Cu cables to 50 mm dia.



- ▶ Exceptional cutting performance even with fine-stranded conductors thanks to specially designed, extremely sharp cutting blades
- ▶ 1000 V fully insulated to IEC 60900

### Characteristics

- Two-hand operation
- Large cutting range
- Not suitable for cutting steel or steel wire

| Technical data  |   |
|---|---|
| Cutting range   | e.g. 4 x 120 mm <sup>2</sup> NYY, max. 50 mm dia. |
| Length  | 710 mm  |
| Weight  | 3.7 kg  |
| Item  | Part No.  |
| Hand-operated cutting tool for Cu and Al cables to 50 mm dia. | <b>K250</b>                                       |



## K 150 Hand-operated cutting tool for Al and Cu cables to 50 mm dia.



- ▶ Exceptional cutting performance even with fine-stranded conductors thanks to specially designed, extremely sharp cutting blades
- ▶ Secure grip due to roughened handle

### Characteristics

- Large cutting range
- Not suitable for cutting steel or steel wire

| Technical data  |   |
|---|---|
| Cutting range   | max. 50 mm dia., e.g. 4 x 120 mm <sup>2</sup> NYY |
| Length  | 710 mm  |
| Weight  | 3 kg  |
| Item  | Part No.  |
| Hand-operated cutting tool for Cu and Al cables to 50 mm dia. | <b>K150</b>                                       |

## K 101/1 Hand-operated cutting tool for Al and Cu cables to 26 mm dia.



- ▶ Can be maintained on-site thanks to replaceable cutting heads
- ▶ Exceptional cutting performance even with fine-stranded conductors

### Characteristics

- Two-hand operation
- Excellent leverage
- Not suitable for cutting steel or steel wire
- Safe working thanks to roughened handle

| Technical data  |  |
|---|--|
| Cutting range   | e.g. 4 x 25 mm <sup>2</sup> NYY, max. 26 mm dia. |
| Length  | 570 mm   |
| Weight  | 1.8 kg   |
| Item  | Part No.   |
| Hand-operated cutting tool for Cu and Al cables to 26 mm dia. | <b>K1011</b>                                     |
| Accessories   | Part No.   |
| Replacement cutting head                                      | K1011E   |