

MAIN CHARACTERISTICS PP60-1 - HP60-3 - AP60-1

| | |
|------------------|--------------------------|
| CRIMPING SECTION | max. 240 mm ² |
| MAXIMUM STROKE | 17 mm |

| | |
|--------------------|------------------|
| CRIMPING FORCE | 60 kN |
| OPERATING PRESSURE | 700 bar (70 MPa) |



Set PP60-1

PP60-1 - Hydraulic crimping head

The unit must be operated through 700 bar hydraulic pump to reach crimping force of 60 kN (pages 201 - 208).

Technical characteristics:

- Sturdy and compact structure
- Openable head to make it easy to position and insert the crimping dies
- Quick make snap lock connection and non detachable dust cap

Tool dimensions: 74 x 198 x 54 mm
 Tool weight: 1,6 kg

| Description | Order No. | Dimensions | Weight |
|-------------------|-----------|-------------------|--------|
| Set crimping head | PP60-1 | 320 x 260 x 75 mm | 2,1 kg |

Set equipment:

- Hydraulic crimping head
- Plastic case for crimping head and maximum 18 crimping dies



Set HP60-3

HP60-3 - Hand operated hydraulic crimping Tool

Technical characteristics:

- Sturdy and compact structure
- Snap closure crimping head, rotates 180°
- Quick feed with double hydraulic cylinder
- Automatic pressure safety valve
- Manual return at any position by turning the main handle

Tool dimensions: 168 x 392 x 54 mm
 Tool weight: 2,5 kg

| Description | Order No. | Dimensions | Weight |
|-------------------|-----------|-------------------|--------|
| Set Crimping Tool | HP60-3 | 440 x 190 x 80 mm | 3,7 kg |

Set equipment:

- Test report
- Manual crimping tool
- Plastic case for manual hydraulic tool and maximum 15 crimping dies