Technical data sheet

Surge protective device for data and information technology



Surge protection for high-speed networks up to 10 GBit (Class EA/CAT6A)






Data cable protection device for high-speed networks

- High-quality RJ45 sockets
- Low protection level at high current load
- Earthing via DIN rail or connection cable
- Support of Power over Ethernet + to 1 A
- Tested transmission quality in networks up to 10 GBit (Class EA) or CAT6A
- Rapid installation through plug-in version
- Incl. DIN rail fastening set and earthing cable


Application example: 10 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces

Туре	Version	Connec-		Weight kg/100 pcs.	Item No.
ND-CAT6A/EA	Fine protection, 8 wires + shield	RJ45 8(8)	1	16,600	5081800

Dimensions



Connection options



ND-CAT6A/EA

ND-OATOA/LA						
Maximum continuous voltage AC V	Uc	41				
Maximum continuous voltage DC V	Uc	58				
Category		Type 2+3 / C2+C1				
Lightning protection zone LPZ		1→3				
Channel performance ISO/IEC		Class EA				
Channel performance Ansi/EA		CAT 6A				
Number of poles		8				
Rated current A	L	1				
Impulse durability wire-wire		C1: 0,3 kV / 0,15 kA (8/20µs)				
Impulse durability wire-earth		C2: 2 kV / 1 kA (8/20µs)				
Total discharge current (8/20) kA		7				
Protection level wire-wire V		<120				
Protection level wire-earth V		<700				
Frequency range		>500 MHz				
Temperature range °C	θ	-40-+80				
Installation type		Connector/cable adapter				
Connection system		RJ45 8(8)				
Protection rating		IP10				
Shielding connection available		Yes				
Shield connection		Direct				
Earthing via:		Connection cable / DIN rail				
Testing standard		IEC 61643-21				